



Powering Business Worldwide

pe.eaton.com

10316 Series, Hazardous Location Limit Switch

10316H2170

UPC:782113452128

Dimensions:

- **Height:** 6.2 IN
- **Length:** 3 IN
- **Width:** 2.54 IN

Weight:1.6813 LB

Notes:1N.O.-1N.C. contacts must be same polarity when both circuits are used - 1N.O.-1N.C. contacts have isolated poles and may be used on opposite polarity. Contact factory for availability of CSA &CE approval status.

Warranties:

- 1 year

Specifications:

- **Connection:** Screw Terminals
- **Contact Rating:** 10A at 600Vac, 0.2A at 125Vdc
- **Contact Configuration:** 1NO-1NC
- **Enclosure Material:** Cast Bronze
- **Environmental Rating:** NEMA 7 Division I Class I BCD, NEMA 9 Division I Class II EFG, NEMA 1, 4, 4X, 13
- **Maximum Ac Current:** 10A
- **Maximum Dc Current:** 0.2A
- **Operating Temperature:** -20° to 200°F (-29° to 93°C)
- **Switch Type:** Top Push Roller

Supporting documents:

- [Eatons Volume 8-Sensing Solutions](#)
- [Eaton Specification Sheet - 10316H2170](#)

Certifications:



- UL Listed
- CSA Certified

Product compliance:

- CE Marked
- Contact Manufacturer

© 2016 Eaton. All rights reserved.