



**MODEL NUMBER**

11-11344-A3

**PRODUCT LINE**

GO™ Switch 10/20 Series

**SPECIFICATIONS**

|                        |                                |
|------------------------|--------------------------------|
| Model                  | 11 Model                       |
| Contact Form           | SPDT (Form C)                  |
| Sensing Range          | Standard approx. 3/8" side     |
| Outlet Position        | Right of sensing area          |
| Enclosure Material     | Stainless steel w/polyurethane |
| Area Classification    | CSA/FM Cl I, Div 1             |
| Wiring Options         | 6ft PVC lead wire              |
| Regional Certification | No regional certification      |
| Custom Field           |                                |

**WIRING DIAGRAM**

PVC/PTFE LEADS - 4 WIRE  
SPDT



**NAMEPLATE**



CL I DIV 1, GRPS A,B,C,D; CL II DIV 1, GRPS E,F,G; CL III;  
T<sub>1</sub>:T<sub>2</sub> - 50°C - T<sub>3</sub> - 60°C/90°C  
ELECTRICAL RATING: 120VAC/10A, 24VDC/3A RESISTIVE; 480VAC/240VDC MAX  
LEAD SEAL IS REQUIRED WITHIN 16" OF ENCLOSURE.

Model #:

Serial #:



www.electrosupply.com  
sales@electrosupply.com  
1-800-663-6576