



Powering Business Worldwide

pe.eaton.com

Photoelectric Sensor

1356A-6513

UPC:782114106877

Dimensions:

- **Height:** 1.64 IN
- **Length:** 3.19 IN
- **Width:** 1.83 IN

Warranties:

- 3 year

Specifications:

- **Type:** Photoelectric Sensor
- **Contact Rating:** 300 mA AC/DC at 20-264 Vac/15-30 Vdc
- **Cable Type:** PVC
- **Contact Configuration:** AC: L1 switched, DC: NPN open collector
- **Cord Length:** 72 FT
- **Enclosure Material:** Noryl
- **Environmental Rating:** NEMA 1, 3, 4, 12, 13
- **Input Voltage:** 20-264 Vac/15-30 Vdc
- **Led Indicators:** Output status
- **Maximum Ac Current:** 300 mA
- **Operating Mode:** Light
- **Operating Temperature:** -40° to 158°F (-40° to 70°C)
- **Sensor Type:** Diffuse Reflective

Supporting documents:

- [Eatons Volume 8-Sensing Solutions](#)
- [Instruction Manual-55 Series Photoelectric Diffuse Reflective, Reflex and Fiber Optic Sensors](#)

Certifications:

- CSA Certified
- UL Listed



Product compliance: No Data

© 2016 Eaton. All rights reserved.