



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Enhanced 50 Series Photoelectric Sensor

1551E-8504

UPC:782116112227

### Dimensions:

- **Height:** 4.16 IN
- **Length:** 1.91 IN
- **Width:** 1.81 IN

**Weight:** .3375 LB

### Warranties:

- 3 year

### Specifications:

- **Connection:** 5 Pin Mini Connector
- **Contact Rating:** 3A at 240 Vac
- **Contact Configuration:** SPDT Form C Relay
- **Enclosure Material:** Fiberglass reinforced plastic
- **Environmental Rating:** IP 67, IP69K
- **Input Voltage:** 12–240 Vdc 24–240 Vac
- **Led Indicators:** Yellow power on, Green outout status, red marginal gain
- **Maximum Ac Current:** 3A
- **Operating Mode:** Fiberoptic, Visible Red
- **Operating Temperature:** -13° to 131°F (-25° to 55°C)
- **Sensor Type:** Fiberoptic
- **Switch Type:** Photoelectric
- **Time Delay:** Yes

### Supporting documents:

- [Eatons Volume 8-Sensing Solutions](#)
- [Eaton Specification Sheet - 1551E-8504](#)

**Certifications:** No Data

**Product compliance:**



- Contact Manufacturer

---

© 2016 Eaton. All rights reserved.