

Alternative article: AC2088

When selecting an alternative article and accessories please note that technical data may differ!


**ecomat300**

AC2018



ACTIVE MODULE UPPER PART

AS-Interface bus system



- 1: label
- 2: pushbutton/LED green
- 3: pushbutton/LED red



Product characteristics

Active module upper parts AS-i illuminated pushbutton module

AS-i interface to FC and SC lower parts

Electrical data

Electrical design	2 pushbuttons / 2 LED displays				
Operating voltage [V]	26.5...31.6 DC				
Total current consumption from AS-i [mA]	< 55				
Inputs digital					
Sensor supply	AS-i				
Environment					
Ambient temperature [°C]	-25...60				
Protection	IP 67				
Tests / approvals					
EMC	EN 50295				
MTTF [Years]	1661				
AS-i classification					
AS-i version	2.1				
Extended addressing mode possible	no				
AS-i profile	S-3.F.F				
I/O configuration [hex]	3				
ID code [Hex]	F.F				
AS-i certificate	04801				
Data bits	<b>Data bit</b>	<b>D0</b>	<b>D1</b>	<b>D2</b>	<b>D3</b>
	Allocation	push-button 2 (red)	push-button 1 (green)	LED 2 (red)	LED 1 (green)
Mechanical data					
Housing materials	PBT (Pocan)				
Weight [kg]	0.095				
Electrical connection					
Connection	contact pins on FC or SC lower module				
Remarks					

**AC2018 - Active module upper parts AS-i illuminated pushbutton module - eclass: 27259090 / 27-25-90-90**

Remarks	The pushbuttons (EAO type 84) provide protection against accidental contact. Housing and pushbuttons can be labelled.
Pack quantity [piece]	1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — AC2018 — 12.02.2015

Alternative article: AC2088

When selecting an alternative article and accessories please note that technical data may differ!