Product data sheet
Characteristics

Electrol
www.electrolsupply.com
sales@electrolsupply.com
1-800-663-6576

AK5PC33L
removable power sockets AK5 - 3P

Product availability : Stock - Normally stocked in distribution facility

Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	3P
[Ith] conventional free air thermal current	32 A
I²t on activation	200000 A².s
Number of points	2
Number of cables	3 cable(s) 0.01 in² (4 mm²)
Cable length	3.28 ft (1 m)
Quantity per set	Set of 6

Complementary

[Ui] rated insulation voltage	600 V conforming to UL 690 V conforming to IEC 60439-1 600 V conforming to CSA
Peak current	25 kA
Width	0.71 in (18 mm)
Height	1.79 in (45.5 mm)
Depth	1.5 in (38 mm)

Environment

Standards	IEC 60439
Product certifications	DNV UL CSA LROS (Lloyds register of shipping)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	22623 - PANEL BUS (AK5)
Discount Schedule	I11
GTIN	00785901576860
Nbr. of units in pkg.	6
Package weight(Lbs)	0.35999999999999999
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period	18 months