



Powering Business Worldwide

pe.eaton.com

22.5 mm Compact Pushbutton

C22-DR-S-K11

Dimensions:

- **Height:** 2.15 IN
- **Length:** 1.17 IN
- **Width:** 1.17 IN

Weight: .06 LB

Notes: Maintained pushbuttons can be converted in the field to momentary operation by switching the locking ring, which is accessible through the side of the operator body.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Pushbutton
- **Action:** Maintained
- **Actuator:** Flush button
- **Bezel:** Silver
- **Button Color:** Black
- **Contact Configuration:** 1NO-1NC
- **Illumination:** Non-Illuminated
- **Size:** 22.5 mm
- **Series:** C22

Supporting documents:

- [C22 Pilot Devices](#)
- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [C22-PVT45P 2D Drawing Xchange](#)
- [Eaton Specification Sheet - C22-DR-S-K11](#)
- [C22-PVT45P 2D PDF](#)
- [C22-PVT45P 3D Inventor](#)
- [C22-PVT45P 3D Model Xchange](#)



- [C22-PVT45P AutoCAD 2D Footprint](#)
- [C22-PVT45P AutoCAD 2D Footprint \(mm\)](#)

Certifications:

- CSA Certified
- IEC 60947
- EN 60947
- UL Listed

Product compliance:

- DIN VDE 0600