



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## 22.5 mm Compact Pushbutton

C22S-DRL-XR-K01-120

### Dimensions:

- **Height:** 2.15 IN
- **Length:** 1.17 IN
- **Width:** 1.17 IN

**Weight:** .1 LB

**Notes:** Maintained pushbuttons can be converted in the field to momentary operation by switching the locking ring, which is accessible through the side of the operator body.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Pushbutton
- **Action:** Maintained
- **Actuator:** Buttonless
- **Bezel:** Black
- **Button Color:** Red without lens
- **Contact Configuration:** 1NC
- **Illumination:** Illuminated
- **Indicator:** LED
- **Size:** 22.5 mm
- **Series:** C22
- **Voltage Rating:** 120V

### Supporting documents:

- [C22 Pilot Devices](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [C22-PVT45P 2D Drawing Xchange](#)
- [Eaton Specification Sheet - C22S-DRL-XR-K01-120](#)



- [C22-PVT45P 2D PDF](#)
- [C22-PVT45P 3D Inventor](#)
- [C22-PVT45P 3D Model Xchange](#)
- [C22-PVT45P AutoCAD 2D Footprint](#)
- [C22-PVT45P AutoCAD 2D Footprint \(mm\)](#)

**Certifications:**

- CSA Certified
- EN 60947
- UL Listed
- IEC 60947

**Product compliance:**

- DIN VDE 0600