



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## 22.5 mm Compact Pushbutton Selector Switch

C22S-WRK3-K11

### Dimensions:

- **Height:** 2.83 IN
- **Length:** 1.17 IN
- **Width:** 1.17 IN

**Weight:** .1 LB

**Notes:** Maintained pushbuttons can be converted in the field to momentary operation by switching the locking ring, which is accessible through the side of the operator body.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Selector Switch
- **Action:** Maintained, 60° V Position
- **Actuator:** Knob
- **Bezel:** Black
- **Button Color:** Black/White
- **Color:** Black/ White
- **Contact Configuration:** 1NO-1NC
- **Illumination:** Non-Illuminated
- **Number Of Positions:** 3-position
- **Size:** 22.5 mm
- **Series:** C22

### Supporting documents:

- [C22 Pilot Devices](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [C22\(S\)-W\(R\)K 2D Drawing Xchange](#)



- [Eaton Specification Sheet - C22S-WRK3-K11](#)
- [C22\(S\)-W\(R\)K 2D PDF](#)
- [C22\(S\)-W\(R\)K 3D Inventor](#)
- [C22\(S\)-W\(R\)K 3D Model Xchange](#)
- [C22\(S\)-W\(R\)K AutoCAD 2D Footprint](#)
- [C22\(S\)-W\(R\)K AutoCAD 2D Footprint \(mm\)](#)

**Certifications:**

- IEC 60947
- UL Listed
- EN 60947
- CSA Certified

**Product compliance:**

- DIN VDE 0600