



Powering Business Worldwide

pe.eaton.com

22.5 mm Compact Pushbutton Selector Switch

C22S-WRS-MS4-K01

Dimensions:

- **Height:** 3.63 IN
- **Length:** 1.17 IN
- **Width:** 1.17 IN

Weight: .1 LB

Notes: Maintained pushbuttons can be converted in the field to momentary operation by switching the locking ring, which is accessible through the side of the operator body.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Selector Switch
- **Action:** Maintained, key removal left/right 40°
- **Actuator:** Key Operated
- **Bezel:** Black
- **Contact Configuration:** 1NC
- **Illumination:** Non-Illuminated
- **Number Of Positions:** 2-position
- **Size:** 22.5 mm
- **Series:** C22

Supporting documents:

- [C22 Pilot Devices](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - C22S-WRS-MS4-K01](#)

Certifications:



- EN 60947
- IEC 60947
- UL Listed
- CSA Certified

Product compliance:

- DIN VDE 0600

© 2016 Eaton. All rights reserved.