



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Definite Purpose Control - Contactor

**C25DRJ350B**

**UPC:**782116484126

### Dimensions:

- **Height:** 3.75 IN
- **Length:** 3.35 IN
- **Width:** 2.4 IN

**Weight:**1.3 LB

### Warranties:

- 1 year

### Specifications:

- **Amperage Rating:** 50A
- **Coil:** 208-240 Vac, 50/60 Hz
- **Enclosure:** Open with DIN rail mounting adapter
- **Frame Size:** 15-50A, two- and three-pole
- **Model:** Contactor
- **Number Of Poles:** Three-pole
- **Resistive Load:** 65A
- **Terminals:** Box lugs (posidrive setscrew) and quick connect terminals (vertical-in-line)
- **Type:** Non-reversing

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [C25DRJ3 3D Inventor](#)
- [Eaton Specification Sheet - C25DRJ350B](#)
- [C25DRJ3 AutoCAD 2D Footprint](#)
- [C25DRJ3 2D Drawing Xchange](#)
- [C25DRJ3 AutoCAD 2D Footprint \(mm\)](#)
- [C25DRJ3 3D Model Xchange](#)
- [C25DRJ3 2D PDF](#)

### Certifications:

- CSA Certified



- UL Recognized

**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.