



## Main

Range	TeSys
Product name	TeSys CASK
Product or component type	Control relay
Device short name	CA2SK
Contactor application	Control circuit
Utilisation category	DC-13 AC-15
Pole contact composition	1 NO + 1 NC
System Voltage	$\leq 690$ V $\leq 400$ Hz
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	110 V AC 50/60 Hz

## Complementary

[Ith] conventional free air thermal current	10 A at $\leq 131$ °F (55 °C)
Associated fuse rating	10 A gL conforming to VDE 0660 10 A gL conforming to IEC 60947
[Ui] rated insulation voltage	690 V conforming to CSA C22.2 No 14 690 V conforming to BS 5424 690 V conforming to IEC 60947 690 V conforming to VDE 0110 group C 690 V conforming to UL 508
Mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1.5...4 mm <sup>2</sup> ) - cable stiffness: solid Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: solid Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (0.5...6 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (0.35...6 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (0.35...1.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end

Screw clamp terminals 2 cable(s) 0...0 in<sup>2</sup> (0.35...2.5 mm<sup>2</sup>) - cable stiffness: flexible - without cable end

Tightening torque	7.08 lbf.in (0.8 N.m) - on screw clamp terminals pozidriv No 1
Control circuit voltage limits	0.85...1.1 Uc at 122 °F (50 °C) operational 0.2...0.75 Uc at 122 °F (50 °C) drop-out
Operating time	6...8 ms coil de-energisation and NO opening 7...14 ms coil energisation and NO closing 8...16 ms coil energisation and NC opening 8...10 ms coil de-energisation and NC closing
Mechanical durability	10 Mcycles
Operating rate	1200 cyc/h
Inrush power in VA	16 VA at 68 °F (20 °C)
Hold-in power consumption in VA	4.2 VA at 68 °F (20 °C)
Heat dissipation	1.4 W
Height	2.2 in (56 mm)
Width	1.06 in (27 mm)
Depth	2.19 in (55.5 mm)
Product weight	0.29 lb(US) (0.132 kg)

## Environment

Standards	NF C 63-110 VDE 0660 IEC 60947 BS 5424
Product certifications	CULus
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Ambient air temperature for storage	-58...158 °F (-50...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating in temperature

## Ordering and shipping details

Category	22371 - RELAYS, CONTROL
Discount Schedule	I12
GTIN	00785901564096
Nbr. of units in pkg.	1
Package weight(Lbs)	0.26000000000000001
Returnability	N
Country of origin	CZ

## Contractual warranty

Warranty period	18 months
-----------------	-----------