



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## D3 Series General Purpose Plug-In Relay

**D3PF2AA**

**UPC:**782113720104

### Dimensions:

- **Height:** 1.39 IN
- **Length:** 2.2 IN
- **Width:** 1.3 IN

**Weight:**.22 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Coil Voltage:** 120V
- **Contact Configuration:** DPDT
- **Contact Material:** Silver alloy
- **Contact Rating:** 16A
- **Cover:** Full featured
- **Enclosure:** IP40
- **Maximum Voltage:** 300V switching
- **Options:** LED test button, flag indicator, lock-down door, finger-grip cover, ID tag
- **Resistance:** 1700 Ohms
- **Series:** D3 series
- **Terminals:** Octal

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [D3\\_F2 3D Inventor](#)
- [Eaton Specification Sheet - D3PF2AA](#)
- [D3\\_F2 AutoCAD 2D Footprint](#)
- [D3\\_F2 AutoCAD 2D Footprint \(mm\)](#)



- [D3\\_F2 2D Drawing Xchange](#)
- [D3\\_F2 2D PDF](#)
- [D3\\_F2 3D Model Xchange](#)

**Certifications:**

- cRUus
- CSA Certified
- UL Listed

**Product compliance:**

- RoHS Compliant
- CE Marked