



MODEL NUMBER

PRODUCT LINE

SPECIFICATIONS

WIRING DIAGRAM

NAMEPLATE



0 Ex ia IIC T4 Ga X; IP66/67  
 -50°C ≤ Ta ≤ 55°C  
 TC RU C-US, FE08.B.02500  
 SWITCH: Ui=16V, Ii=25mA, Pi=64mW (Reference Cert for Ci and Li)

Telemetry Equipment for use in Hazardous Locations  
**WARNING:** Substitution of components may impair intrinsic safety. The installer shall confirm which certified sub-assemblies are fitted and ensure compliance with the entry parameters in the appropriate certificate. Potential electrostatic charging hazard - Clean only with damp cloth.



TopWorX  
 3300 Fern Valley Road  
 Louisville, KY 40213 USA  
 www.topworx.com

Serial #:

DXP-E20GMB000R

Switchbox DXP and DXS

Equipment: TopWorX  
 Rev. Number: 01/17  
 Rev. Description: Updated to reflect changes to the IEC 60079-10:2015 standard  
 Issue Date: 01/17  
 Certified Person: [Signature]  
 Title: [Title]  
 Date: [Date]  
 Drawn By: [Name]  
 Checked By: [Name]  
 Approved By: [Name]

**Electrol**

www.electrosupply.com  
 sales@electrosupply.com  
 1-800-663-6576