

no longer available - archive entry replaced by: EVC072


ecomat 400

E10968



ADOGH050MSS0010H05

Connection technology



Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

Free from halogen

gold-plated contacts

Electrical data

Electrical design

Operating voltage [V]

[M]

AC/DC

30 AC / 36 DC

Current rating [A]

[A]

4

Environment

Ambient temperature [°C]

[°C]

-25...90

Protection

IP 68

Mechanical data

Design

straight

Material body

TPU (urethane)

Material nut

brass; nickel-plated

Tightening torque for knurled nut [Nm]

0.5

Weight [kg]

[kg]

0.371

Electrical connection

Connection

PUR cable / 10 m;

5 x 0.34 mm² (42 x Ø 0.1 mm); Ø 5.5 mm; halogen-free

Sheath color

black

Wiring

Core colors


BK black

BN brown

BU blue

GY grey

WH white



1 BN

2 WH

3 BU

4 BK

5 GY

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — E10968 — 12.01.2004

no longer available - archive entry replaced by: EVC072