

no longer available - archive entry Alternative article: E20165

When selecting an alternative article and accessories please note that technical data may differ!


efector200

E20167



FE-30-P-A-R3

Fiber optics



Product characteristics

Through-beam sensor

Ø 3 mm

Sensing range 100 mm

Connection to fibre optic amplifiers type OIF

Monitoring range

| | |
|---------------|-------------|
| Sensing range | OIF: 100 mm |
|---------------|-------------|

Environment

| | |
|--------------------------|----------|
| Ambient temperature [°C] | -20...80 |
|--------------------------|----------|

Mechanical data

| | |
|--------|--------|
| Design | angled |
|--------|--------|

| | |
|-------------|-----|
| Length [mm] | 600 |
|-------------|-----|

| | |
|--------------------------|----|
| Min. bending radius [mm] | 30 |
|--------------------------|----|

Fiber arrangement



Fiber optic

glass

Sensing head

aluminum

Sheathing

PVC; adapter: polyamide

| | |
|-------------|-------|
| Weight [kg] | 0.072 |
|-------------|-------|

0.072

Accessories

| | |
|------------------------|--------|
| Accessories (included) | E20104 |
|------------------------|--------|

Remarks

| | |
|-----------------------|---|
| Pack quantity [piece] | 1 |
|-----------------------|---|

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — E20167 — 04.06.2003

no longer available - archive entry Alternative article: E20165

When selecting an alternative article and accessories please note that technical data may differ!