


EVC008

ADOAH043MSS0005H04

Connection technology



Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

Free from halogen

gold-plated contacts

Electrical data

Electrical design		DC PNP
Operating voltage	[V]	10...36 DC
Current rating	[A]	4
Protection class		II

Environment

Ambient temperature	[°C]	-25...90, cULus: max. 75 °C
Ambient temperature (moving)	[°C]	-25...90, cULus: max. 75 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

Tests / approvals

MTTF	[Years]	20027
------	---------	-------

Mechanical data

Design		angled
Material body		housing: TPU (urethane) black transparent; sealing: Viton
Material nut		brass; nickel-plated
Tightening torque for knurled nut [Nm]		0.6...1.5
Drag chain suitability		<p>Bending radius for flexible applications:</p> <p>min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s²</p> <p>Travel speed: of 5 m/s²</p> <p>Bending cycles: > 5 million</p> <p>Torsional strain: ± 180 °/m</p>
Weight	[kg]	0.178

Displays / operating elements

Output status indication	LED	2 x yellow
Power	LED	green

Electrical connection

Connection		PUR cable / 5 m; 4 x 0.34 mm ² (42 x Ø 0.1 mm); Ø 4.9 mm; halogen-free
Sheath color		black



EVC008



ADOAH043MSS0005H04

Connection technology

Wiring

Core colors

BK black
BN brown
BU blue
WH white



Remarks

Pack quantity [piece] 1