



Main

Range	TeSys
Product or component type	Auxiliary contact block
Product compatibility	GV7RE GV7RS

Complementary

Auxiliary contacts operation	Standard
Pole contact composition	1 C/O
[Ui] rated insulation voltage	690 V - for control circuit - conforming to IEC 60947-1
System Voltage	110 V AC control circuit 110 V DC control circuit 230...240 V AC control circuit 24 V AC control circuit 24 V DC control circuit 250 V DC control circuit 380...415 V AC control circuit 440 V AC control circuit 48 V AC control circuit 48 V DC control circuit 690 V AC control circuit
Mechanical durability	50000 cycles
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Connections - terminals	Control circuit: connector 1 cable 0 in ² (1.5 mm ²) - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 0 in ² (1.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: connector 1 cable 0 in ² (1.5 mm ²) - cable stiffness: solid
Product weight	0.03 lb(US) (0.015 kg)

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11

GTIN	00785901566908
Nbr. of units in pkg.	1
Package weight(Lbs)	5.9999999999999998E-2
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------