

no longer available - archive entry Alternative article: IG6052

When selecting an alternative article and accessories please note that technical data may differ!


efectorio

IA5058



IA-3010-BNKG

Inductive sensors



Product characteristics

Inductive sensor

Plastic housing Ø 20 mm

Cable

Sensing range 10 mm; [nf] non-flush mountable

Electrical data

Electrical design

DC NPN

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally closed

Voltage drop [V]

< 2.5

Current rating [mA]

250

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

300

Monitoring range

Sensing range [mm]

10

Real sensing range (Sr) [mm]

10 ± 10 %

Operating distance [mm]

0...8.1

Accuracy / deviations

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

1781

Mechanical data

Mounting

non-flush mountable

Housing materials

PBT

Weight [kg]

0.174

Displays / operating elements

Output status indication LED

yellow

Electrical connection

Connection

PVC cable / 2 m; 3 x 0.5 mm²

Wiring


IA5058 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Core colors

BN brown

BU blue

BK black



Accessories

Accessories (included)

Mounting clamp

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — IA5058 — 06.03.2003

no longer available - archive entryAlternative article: IG6052

When selecting an alternative article and accessories please note that technical data may differ!