


no longer available - archive entry

efector100

IA8501



Inductive sensors



Product characteristics

Inductive sensor

Plastic housing Ø 20 mm

Cable with connector

Sensing range 10 mm; [nrf] non-flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

250

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

300

Monitoring range

Sensing range [mm]

10

Real sensing range (Sr) [mm]

10 ± 10 %

Operating distance [mm]

0...8.1

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

Mechanical data

Mounting

non-flush mountable

Housing materials

PBT

Displays / operating elements

Output status indication LED

yellow


Electrical connection

Connection

PVC cable / 2 m; 3 x 0.5 mm²; with M12 connector

Wiring

IA8501 - Inductive sensor - eclass: 27270101 / 27-27-01-01



Accessories

Accessories (included)

Mounting clamp

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — IA8501 — 26.10.2005
no longer available - archive entry