

Product characteristics

Inductive sensor

Metal thread M8 x 1

Cable

Sensing range 1 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

III

Reverse polarity protection

no

Outputs

Output function

normally closed

Voltage drop [V]

< 1

Current rating [mA]

200

Short-circuit protection

no

Overload protection

no

Switching frequency [Hz]

750; (1000 nb)

Monitoring range

Sensing range [mm]

1

Real sensing range (Sr) [mm]

1 ± 10 %

Operating distance [mm]

0...0.8

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

5623

Mechanical data

Mounting

flush mountable

Housing materials

brass white bronze coated; PBT

Weight [kg]

0.052

Displays / operating elements

Output status indication LED

yellow

Electrical connection

Connection


PVC cable / 2 m; 3 x 0.14 mm<sup>2</sup>

**Wiring**

# IE5078 - Inductive sensor - eclass: 27270101 / 27-27-01-01

## Core colors

BN brown  
BU blue  
BK black



## Accessories

Accessories (included)

2 lock nuts

## Remarks

Pack quantity

[piece]

1