

Product characteristics

Inductive sensor

Metal thread M8 x 1

Cable

Sensing range 1 mm; [f] flush mountable

Electrical data

Electrical design

Operating voltage [V]

Current consumption [mA]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Current rating [mA]

Short-circuit protection

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [mm]

Real sensing range (Sr) [mm]

Operating distance [mm]

Accuracy / deviations

Correction factors

Hysteresis [% of Sr]

Switch-point drift [% of Sr]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

MTTF [Years]

Mechanical data

Mounting

Housing materials

Weight [kg]

Displays / operating elements

Output status indication LED

Electrical connection

Connection

Wiring

DC PNP

10...36 DC

10 (24 V)

II

no

normally open

< 1

200

no

no

750; (1000 nb)

1

1 ± 10 %

0...0.8

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.4 / copper approx. 0.3

3...15

-10...10

-25...80

IP 67

5542

flush mountable

brass nickel-plated; PBT

0.052


yellow

PUR cable / 2 m; 3 x 0.14 mm²; highly flexible

IE5199 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Core colors

BK black
BN brown
BU blue



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1