

Product characteristics

Inductive sensor

Metal thread M8 x 1

Cable with connector

Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

**Current rating**

- Current rating (continuous) [mA]

250

- Current rating (peak) [mA]

250

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

1000

Monitoring range

Sensing range [mm]

2

Real sensing range (Sr) [mm]

2 ± 10 %

Operating distance [mm]

0...1.62

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...70

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

3502

Mechanical data


Mounting

flush mountable

# IE5324 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Housing materials	brass white bronze coated; LCP
Weight [kg]	0.041
Displays / operating elements	
Output status indication LED	red
Electrical connection	
Connection	PUR cable / 0.8 m; 3 x 0.14 mm <sup>2</sup> ; flame-retardant (FRNC), with M12 connector, rotatable

## Wiring



Accessories	
Accessories (included)	2 lock nuts
Remarks	
Pack quantity [piece]	1