



Product characteristics

Inductive sensor

Metal thread M8 x 1

Quick disconnect

Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

< 15

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

100

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

1000

Monitoring range

Sensing range [mm]

2

Real sensing range (Sr) [mm]

2 ± 10 %

Operating distance [mm]

0...1.62

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

0...100

Protection

IP 68 / IP 69K

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

2751

Mechanical data

Mounting

flush mountable

Housing materials

housing: high-grade stainless steel; active face: PEEK (polyether ether ketone)

Weight [kg]

0.021

Displays / operating elements

Output status indication LED

yellow (4 x 90°)

Electrical connection

Connection

M12 connector

Wiring

IE5379 - Inductive sensor - eclass: 27270101 / 27-27-01-01



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1