

no longer available - archive entry Alternative article: IF5721

When selecting an alternative article and accessories please note that technical data may differ!


**efectorio**

IF5872



IFC2002-ARKG/UP/6M/PH V01

Inductive sensors



Product characteristics

Inductive sensor

Plastic thread M12 x 1

Cable

Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

10...36 DC

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 4.6

Minimum load current [mA]

4

Leakage current [mA]

< 0.6

Current rating [mA]

150

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

1200

Monitoring range

Sensing range [mm]

2

Real sensing range (Sr) [mm]

2 ± 10 %

Operating distance [mm]

0...1.6

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

2744

Mechanical data

Mounting

flush mountable

Housing materials

PBT

Weight [kg]

0.224

Displays / operating elements

Output status indication LED

yellow

Electrical connection


Connection

PUR / PVC cable / 6 m; 2 x 0.34 mm<sup>2</sup>

**Wiring**

# IF5872 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Core colors  
BK black  
WH white



## Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — IF5872 — 06.03.2003

no longer available - archive entryAlternative article: IF5721

When selecting an alternative article and accessories please note that technical data may differ!