

Product characteristics

Inductive sensor

Plastic thread M18 x 1

Cable

Sensing range 5 mm; [f] flush mountable

Electrical data

Electrical design

Operating voltage [V]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Minimum load current [mA]

Leakage current [mA]

**Current rating**

- Current rating (continuous) [mA]

- Current rating (peak) [mA]

Short-circuit proof

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [mm]

Real sensing range (Sr) [mm]

Operating distance [mm]

Accuracy / deviations

Correction factors

Hysteresis [% of Sr]

Switch-point drift [% of Sr]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

EMC

MTTF [Years]

Mechanical data

Mounting

Housing materials

Weight [kg]

Displays / operating elements

Output status indication LED

Electrical connection

AC/DC

20...250 AC/DC

II

no

normally open

< 6.5 AC / < 6 DC

5

< 2.5 (250 V AC) / < 1.3 (110 V AC) / < 0.8 (24 V DC)

250 AC / 100 DC; 350 AC (...50 °C)

î: 2.2 A (20 ms / 0.5 Hz)

no

no

25 AC / 50 DC

5

5 ± 10 %

0...4.05

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

1...15

-10...10

-25...80

IP 67

EN 60947-5-2

EN 55011: class B

609

flush mountable

PBT

0.112

red

# IG0325 - Inductive sensor - eclass: 27270101 / 27-27-01-01


Connection	PVC cable / 2 m; 2 x 0.5 mm <sup>2</sup>
------------	--

**Wiring**

Core colors

BN brown

BU blue



Note: miniature fuse to IEC60127-2 sheet 1,  
 $\leq 2$  A (fast acting)

Accessories	
-------------	--

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks	
---------	--

Remarks	Recommendation: check the unit for reliable function after a short circuit.
---------	---

Pack quantity	[piece]	1
---------------	---------	---