

Product characteristics

Inductive sensor

Metal thread M18 x 1

Quick disconnect

Sensing range 8 mm; [nrf] non-flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

18...36 DC

Current consumption [mA]

15 (24 V)

Protection class

II

Reverse polarity protection

no

Outputs

Output function

normally closed

Voltage drop [V]

< 2.5

Current rating [mA]

120; 150 (...50 °C)

Short-circuit protection

no

Overload protection

no

Switching frequency [Hz]

200

Monitoring range

Sensing range [mm]

8

Real sensing range (Sr) [mm]

8 ± 10 %

Operating distance [mm]

0...6.5

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011: class B

MTTF [Years]

1528

UL approval number

A001

Mechanical data

Mounting

non-flush mountable

Housing materials

brass white bronze coated; active face: PC (polycarbonate)

Weight [kg]

0.05

Displays / operating elements

Output status indication LED

yellow


Electrical connection

Connection

M12 connector

IG5319 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Wiring



Accessories	
Accessories (included)	2 lock nuts
Remarks	
Pack quantity	[piece] 1