

Product characteristics

Inductive sensor

Metal thread M18 x 1

Quick disconnect

gold-plated contacts

Sensing range 5 mm; [f] flush mountable

Electrical data

Electrical design

DC NPN

Operating voltage [V]

10...30 DC

Current consumption [mA]

< 10

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

100

Short-circuit protection

yes

Overload protection

yes

Switching frequency [Hz]

500

Monitoring range

Sensing range [mm]

5

Real sensing range (Sr) [mm]

5 ± 10 %

Operating distance [mm]

0...4.05

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

3...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...80

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

1587

Mechanical data

Mounting

flush mountable

Housing materials

brass white bronze coated; active face: PBT orange; LED window: PEI; lock nuts: brass white bronze coated

Weight [kg]

0.052

Displays / operating elements

Output status indication LED

4 x red



Electrical connection

Connection

M12 connector; gold-plated contacts

Wiring

IG5795 - Inductive sensor - eclass: 27270101 / 27-27-01-01



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1