

Product characteristics

Inductive sensor

Metal thread M18 x 1

Cable

Increased sensing range

Optical setting aid (2 LED)

Sensing range 8 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

10...36 DC

Protection class

II

Reverse polarity protection

no

Outputs

Output function

normally open

Voltage drop [V]

< 5

Minimum load current [mA]

5

Leakage current [mA]

< 1

Current rating [mA]

100

Short-circuit protection

no

Overload protection

no

Switching frequency [Hz]

100

Monitoring range

Sensing range [mm]

8

Real sensing range (Sr) [mm]

8 ± 10 %

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

3...15

Environment

Ambient temperature [°C]

-25...70

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

1522

Mechanical data

Mounting

flush mountable

Housing materials

brass white bronze coated; PBT

Weight [kg]

0.189

Displays / operating elements

Output status indication LED

1 x red / 1 x green

Electrical connection


Connection

PUR / PVC cable / 3 m; 2 x 0.50 mm²

Wiring

IG5820 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Core colors
BK black



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1