

Product characteristics

Inductive sensor

Metal thread M18 x 1

Quick disconnect

Increased sensing range

Sensing range 8 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

10...55 DC

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open / closed programmable

Voltage drop [V]

< 4.6

Minimum load current [mA]

4

Leakage current [mA]

< 0.8

Current rating [mA]

400

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

250

Monitoring range

Sensing range [mm]

8

Operating distance [mm]

0...6.48

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Environment

Ambient temperature [°C]

-25...70

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011: class B

MTTF [Years]

1806

Mechanical data

Mounting

flush mountable

Housing materials

brass white bronze coated; CO-PC

Weight [kg]

0.064

Displays / operating elements

Output status indication LED

yellow



Electrical connection

Connection

M12 connector

Wiring

IG5958 - Inductive sensor - eclass: 27270101 / 27-27-01-01



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — IG5958 — 13.07.2004