

Product characteristics

Inductive sensor

Metal thread M18 x 1

Quick disconnect

Operation as 3-wire or 2-wire possible

Increased sensing range

Optical setting aid (2 LED)

gold-plated contacts

Sensing range 12 mm; [nfl] non-flush mountable

Electrical data

Electrical design

3-wire DC PNP; 2-wire DC PNP/NPN

Operating voltage [V]

10...30 DC

Current consumption [mA]

12 (24 V)

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.8

Minimum load current [mA]

2; only in 2-wire operation

Leakage current [mA]

< 0.5; only in 2-wire operation

Current rating [mA]

100

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

300

Monitoring range

Sensing range [mm]

12

Real sensing range (Sr) [mm]

12 ± 10 %

Operating distance [mm]

0...9.7

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

3...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...70

Protection

IP 67

Tests / approvals

EMC

EN 61000-4-2 ESD: 4 kV CD / 8 kV AD

EN 61000-4-3 HF radiated: 10 V/m

EN 61000-4-4 Burst: 2 kV

EN 61000-4-6 HF conducted: 10 V

EN 55011: class B

MTTF [Years]



1359

IGS209 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Mechanical data

Mounting		non-flush mountable
Housing materials		brass white bronze coated; active face: PBT (Pocan)
Weight	[kg]	0.055
Displays / operating elements		
Output status indication	LED	yellow (4 x 90°)
Setting aid	LED	red
Electrical connection		
Connection		M12 connector; gold-plated contacts

Wiring



Accessories

Accessories (included)		2 lock nuts
Remarks		
Remarks		suitable for PLC type 1 according to IEC 61131-2
Pack quantity	[piece]	1