

Product characteristics

Inductive sensor

Metal thread M30 x 1.5

Cable

Sensing range 10 mm; [f] flush mountable

Electrical data

Electrical design

Operating voltage [V]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Minimum load current [mA]

Leakage current [mA]

Current rating

- Current rating (continuous) [mA]

- Current rating (peak) [mA]

Short-circuit proof

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [mm]

Real sensing range (Sr) [mm]

Operating distance [mm]

Accuracy / deviations

Correction factors

Hysteresis [% of Sr]

Switch-point drift [% of Sr]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

EMC

MTTF [Years]

Mechanical data

Mounting

Housing materials

Weight [kg]

Displays / operating elements

Output status indication

	AC/DC
Operating voltage [V]	20...250 AC/DC
Protection class	II
Reverse polarity protection	no
Output function	normally open
Voltage drop [V]	< 6.5 AC / < 6 DC
Minimum load current [mA]	5
Leakage current [mA]	< 2.5 (250 V AC) / < 1.3 (110 V AC) / < 0.8 (24 V DC)
- Current rating (continuous) [mA]	250 AC / 100 DC; 350 AC (...50 °C)
- Current rating (peak) [mA]	\hat{i} : 2.2 A (20 ms / 0.5 Hz)
Short-circuit proof	no
Overload protection	no
Switching frequency [Hz]	25 AC / 50 DC
Sensing range [mm]	10
Real sensing range (Sr) [mm]	10 ± 10 %
Operating distance [mm]	0...8.1
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10
Ambient temperature [°C]	-25...80
Protection	IP 67
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	607
Mounting	flush mountable
Housing materials	stainless steel 316Ti / 1.4571; PBT (Pocan) uncolored
Weight [kg]	0.258
Output status indication	yellow

II0250 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Electrical connection

Connection


PVC cable / 2 m; 2 x 0.5 mm²

Wiring

Core colors

BN brown

BU blue



Note: miniature fuse to IEC60127-2 sheet 1,
≤ 2 A (fast acting)

Accessories

Accessories (included)

2 lock nuts

Remarks

Remarks

Recommendation: check the unit for reliable function after a short circuit.

Pack quantity [piece]

1