

Product characteristics

Inductive sensor	
Metal thread M30 x 1.5	
Cable	
Sensing range 10 mm; [f] flush mountable	
Electrical data	
Electrical design DC PNP	
Operating voltage [V]	10...36 DC
Current consumption [mA]	15 (24 V)
Protection class	II
Reverse polarity protection	yes
Outputs	
Output function	complementary
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	400
Monitoring range	
Sensing range [mm]	10
Real sensing range (Sr) [mm]	10 ± 10 %
Operating distance [mm]	0...8.1
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3
Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10
Environment	
Ambient temperature [°C]	-25...80
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1365
Mechanical data	
Mounting	flush mountable
Housing materials	brass nickel-plated; PBT (Pocan)
Weight [kg]	0.231
Displays / operating elements	
Output status indication LED	yellow

II5162 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Electrical connection

Connection

PVC cable / 2 m; 4 x 0.34 mm²

Wiring


Core colors

BK black

BN brown

BU blue

WH white



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1