


Product characteristics

Inductive sensor	
Metal thread M30 x 1.5	
Quick disconnect	
gold-plated contacts	
Sensing range 15 mm; [nf] non-flush mountable	
Electrical data	
Electrical design	DC PNP
Operating voltage [V]	10...55 DC
Current consumption [mA]	15 (24 V)
Protection class	III
Reverse polarity protection	yes
Outputs	
Output function	normally closed
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	yes
Overload protection	yes
Switching frequency [Hz]	200
Monitoring range	
Sensing range [mm]	15
Real sensing range (Sr) [mm]	15 ± 10 %
Operating distance [mm]	0...12.15
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3
Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10
Environment	
Ambient temperature [°C]	-25...80
Protection	IP 65 / IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1745
Mechanical data	
Mounting	non-flush mountable
Housing materials	stainless steel (303S22); PBT
Weight [kg]	0.151
Displays / operating elements	
Output status indication LED	yellow
Electrical connection	
Connection	M12 connector; gold-plated contacts

II5665 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Wiring



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1