



Product characteristics

Inductive sensor	
Plastic thread M30 x 1.5	
Cable	
Sensing range 15 mm; [nf] non-flush mountable	
Electrical data	
Electrical design	DC PNP/NPN
Operating voltage [V]	10...55 DC
Protection class	II
Reverse polarity protection	yes
Outputs	
Output function	normally open / closed programmable
Voltage drop [V]	< 4.6
Minimum load current [mA]	4
Leakage current [mA]	< 0.5
Current rating [mA]	400
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	200
Monitoring range	
Sensing range [mm]	15
Real sensing range (Sr) [mm]	15 ± 10 %
Operating distance [mm]	0...12.1
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10
Environment	
Ambient temperature [°C]	-25...80
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1835
Mechanical data	
Mounting	non-flush mountable
Housing materials	PBT
Weight [kg]	0.172
Displays / operating elements	
Output status indication LED	red
Electrical connection	
Connection	PUR / PVC cable / 2 m; 2 x 0.5 mm ²

II5736 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Wiring

Core colors

BK black

WH white



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1