



Product characteristics

Inductive sensor	
Metal thread M30 x 1.5	
Quick disconnect	
Increased sensing range	
Sensing range 15 mm; [f] flush mountable	
Electrical data	
Electrical design	DC PNP
Operating voltage [V]	10...36 DC
Current consumption [mA]	15 (24 V)
Protection class	II
Reverse polarity protection	yes
Outputs	
Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	250
Monitoring range	
Sensing range [mm]	15
Operating distance [mm]	0...12.1
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
Hysteresis [% of Sr]	1...15
Environment	
Ambient temperature [°C]	-25...70
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
Mechanical data	
Mounting	flush mountable
Housing materials	brass white bronze coated; PBT (Pocan) uncolored
Displays / operating elements	
Output status indication LED	yellow (4 x 90°)
Electrical connection	
Connection	M12 connector

Wiring

II8501 - Inductive sensor - eclass: 27270101 / 27-27-01-01



Accessories

Accessories (included)

2 lock nuts; Socket W94005

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — II8501 — 13.09.2005