

Product characteristics

Inductive sensor
Metal thread M30 x 1.5
Quick disconnect
Increased sensing range
gold-plated contacts
Sensing range 15 mm; [f] flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC
Current consumption [mA]	< 10
Protection class	II
Reverse polarity protection	yes

Outputs

Output function	normally closed
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	yes
Overload protection	yes
Switching frequency [Hz]	100

Monitoring range

Sensing range [mm]	15
Real sensing range (Sr) [mm]	15 ± 10 %
Operating distance [mm]	0...12.15

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3
--------------------	---

Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-25...70
Protection	IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V EN 55011: class B
-----	---

MTTF [Years]	1528
--------------	------

UL approval number	A001
--------------------	------


Mechanical data

Mounting	flush mountable
----------	-----------------

IIS208 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Housing materials	brass white bronze coated; active face: PBT orange; LED window: PEI; lock nuts: brass white bronze coated
Weight [kg]	0.119
Displays / operating elements	
Output status indication LED	4 x yellow
Electrical connection	
Connection	M12 connector; gold-plated contacts

Wiring



Accessories	
Accessories (included)	2 lock nuts
Remarks	
Pack quantity [piece]	1