

Product characteristics

Inductive sensor	
Metal thread M30 x 1.5	
Quick disconnect	
Increased sensing range	
gold-plated contacts	
Sensing range 15 mm; [f] flush mountable	
Electrical data	
Electrical design DC PNP	
Operating voltage [V]	10...36 DC
Current consumption [mA]	< 10
Protection class	II
Reverse polarity protection	yes
Outputs	
Output function	normally closed
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	100
Monitoring range	
Sensing range [mm]	15
Operating distance [mm]	0...12.1
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.5 / Cu approx. 0.4
Hysteresis [% of Sr]	1...20
Environment	
Ambient temperature [°C]	0...100
Protection	IP 68 / IP 69K
Tests / approvals	
EMC	
	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated: 10 V/m
	EN 61000-4-4 Burst: 2 kV
	EN 61000-4-5 Surge: 0.5 kV
	EN 61000-4-6 HF conducted: 10 V
	EN 55011: class B
MTTF [Years]	1590
Mechanical data	
Mounting	flush mountable
Housing materials	stainless steel (316L); active face: PEEK (polyether ether ketone)
Weight [kg]	0.131
Displays / operating elements	


# IIT218 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Output status indication LED | yellow (4 x 90°)

Electrical connection

Connection | M12 connector; gold-plated contacts

## Wiring



## Accessories

Accessories (included) | 2 lock nuts

Remarks

Pack quantity [piece] | 1