

Product characteristics

Inductive sensor

Metal housing Ø 6.5 mm

Quick disconnect

Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC; cULus - Class 2 source required

Current consumption [mA]

< 15

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

200

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

1000

Monitoring range

Sensing range [mm]

2

Real sensing range (Sr) [mm]

2 ± 10 %

Operating distance [mm]

0...1.62

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...70

Protection

IP 67; if screwed on

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

2935

Mechanical data

Mounting

flush mountable

Housing materials

housing: high-grade stainless steel; active face: PBT

Weight [kg]

0.017

Displays / operating elements



IT5048 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Output status indication	LED	yellow (4 x 90°)
--------------------------	-----	------------------

Electrical connection		
-----------------------	--	--

Connection		M8 connector
------------	--	--------------

Wiring



Accessories		
-------------	--	--

Accessories (included)		Mounting clamp
------------------------	--	----------------

Remarks		
---------	--	--

Pack quantity	[piece]	1
---------------	---------	---