

Product characteristics

Inductive sensor

Metal thread M5 x 0.5

Cable

Sensing range 1.2 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...30 DC

Current consumption [mA]

< 15

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

100

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

2000

Monitoring range

Sensing range [mm]

1.2

Operating distance [mm]

0...0.97

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3

Hysteresis [% of Sr]

1...15

Environment

Ambient temperature [°C]

-25...70

Protection

IP 65

Tests / approvals

EMC

EN 60947-5-2

MTTF

[Years]

951

Mechanical data

Mounting

flush mountable

Housing materials

stainless steel (303S22); POM (polyoxymethylene)

Weight [kg]

0.036

Displays / operating elements

Output status indication LED

yellow

Electrical connection

Connection


PUR cable / 2 m; 3 x 0.14 mm²

Wiring

IY5052 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Core colors

BK black
BN brown
BU blue



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1