


IZB30.8-APKG/V2A

Inductive sensors



**Product characteristics**  
Inductive sensor

Metal housing Ø 4 mm

Cable

Sensing range 0.8 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally closed

Voltage drop [V]

< 2.5

Current rating [mA]

100

Short-circuit protection

yes (non-latching)

Overload protection

yes

Switching frequency [Hz]

2000

Monitoring range

Sensing range [mm]

0.8

Real sensing range (Sr) [mm]

0.8 ± 10 %

Operating distance [mm]

0...0.65

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...70

Protection

IP 65

Tests / approvals

EMC

EN 60947-5-2

MTTF [Years]

953

Mechanical data

Mounting

flush mountable

Housing materials

stainless steel (303S22); POM (polyoxymethylene)

Weight [kg]

0.047

Displays / operating elements

Output status indication LED

yellow

Electrical connection

Connection

PVC cable / 2 m; 3 x 0.14 mm<sup>2</sup>

**Wiring**


# IZ5031 - Inductive sensor - eclass: 27270101 / 27-27-01-01

## Core colors

BN brown

BU blue

BK black



## Accessories

Accessories (included)

Mounting clamp

## Remarks

Pack quantity

[piece]

1