

Product characteristics

Capacitive sensor

Rectangular, plastics

Cable

Increased immunity to conducted radio frequency interference

Sensing range 60 mm; [nf] non-flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

250

Short-circuit proof

yes

Overload protection

yes

Switching frequency [Hz]

10

Monitoring range

Sensing range [mm]

60

Real sensing range (Sr) [mm]

60 ± 10 %

Operating distance [mm]

0...48.6

Accuracy / deviations

Correction factors

water = 1 / glass approx. 0.4 / ceramics approx. 0.2 / PVC approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-15...15

Environment

Ambient temperature [°C]

-25...50

Protection

IP 65

Tests / approvals

EMC

IEC 60947-5-2:

2007

MTTF [Years]

615

Mechanical data

Mounting

non-flush mountable

Housing materials

modified PPO

Weight [kg]

0.404

Displays / operating elements

KD5022 - Capacitive sensor - eclass: 27270102 / 27-27-01-02

Output status indication	LED	yellow
--------------------------	-----	--------

Electrical connection		
-----------------------	--	--

Connection		PVC cable / 2 m; 3 x 0.5 mm ²
------------	--	--


Wiring

Core colors

BN brown

BK black

BU blue



Accessories		
-------------	--	--

Accessories (included)		screwdriver
------------------------	--	-------------

Remarks		
---------	--	--

Pack quantity	[piece]	1
---------------	---------	---