

Product characteristics

Capacitive sensor

Plastic thread M30 x 1.5

Cable

Increased immunity to conducted radio frequency interference

Sensing range 15 mm; adjustable 3...15 mm; [nf] non-flush mountable

Electrical data

Electrical design

Operating voltage [V]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Minimum load current [mA]

Leakage current [mA]

Current rating

- Current rating (continuous) [mA]

- Current rating (peak) [mA]

Short-circuit proof

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [mm]

Real sensing range (Sr) [mm]

Operating distance [mm]

Accuracy / deviations

Correction factors

Hysteresis [% of Sr]

Switch-point drift [% of Sr]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

EMC

MTTF [Years]

Mechanical data

Mounting

Housing materials

Weight [kg]

Displays / operating elements

Output status indication LED

Electrical connection

Connection

AC/DC

20...250 AC/DC

II

no

normally closed

< 10 AC / < 8 DC

5

< 2.5 (250 V AC) / < 1.7 (110 V AC) / < 1.5 (24 V DC)

200; für UL-Applikation: 200 AC / 100 DC

î: 1.5 A (20 ms / 0.5 Hz)

no

no

25 AC / 40 DC

15, adjustable 3...15 mm

15 ± 10 %

0...12.1

water = 1 / glass approx. 0.4 / ceramics approx. 0.2 / PVC approx. 0.2

1...15

-15...15

-25...70

IP 65

IEC 60947-5-2:

2007

489

non-flush mountable

PBT

0.14

red

PVC cable / 2 m; 2 x 0.5 mm²


KI0203 - Capacitive sensor - eclass: 27270102 / 27-27-01-02

Wiring

Core colors

BN brown

BU blue



Note: miniature fuse to IEC60127-2 sheet 1,
 ≤ 2 A (fast acting)

Accessories

Accessories (included)

2 lock nuts; screwdriver

Remarks

Remarks

Recommendation: check the unit for reliable function after a short circuit.

Pack quantity

[piece]

1