

Product characteristics

Capacitive sensor

Plastic thread M30 x 1.5

Cable with connector

Sensing range 15 mm; adjustable 3...15 mm; [nf] non-flush mountable

Electrical data

Electrical design

DC NPN

Operating voltage [V]

10...36 DC

Current consumption [mA]

< 15

Protection class

II

Reverse polarity protection

yes

Outputs

Output function

normally open / closed programmable

Voltage drop [V]

< 2.5

Current rating

- Current rating (continuous) [mA]

250

- Current rating (peak) [mA]

250

Short-circuit proof

yes

Overload protection

yes

Switching frequency [Hz]

40

Monitoring range

Sensing range [mm]

15, adjustable 3...15 mm

Real sensing range (Sr) [mm]

15 ± 10 %

Operating distance [mm]

0...12.1

Accuracy / deviations

Correction factors

water = 1 / glass approx. 0.4 / ceramics approx. 0.2 / PVC approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-15...15

Environment

Ambient temperature [°C]

-25...80

Protection

IP 65

Tests / approvals

MTTF

[Years]

694

Mechanical data

Mounting

non-flush mountable

Housing materials

PBT

Weight [kg]

0.11

Displays / operating elements

Output status indication

LED

red



Electrical connection

Connection

PUR cable / 0.1 m; with M12 connector

Wiring

KI5210 - Capacitive sensor - eclass: 27270102 / 27-27-01-02



Accessories

Accessories (included)

2 lock nuts; screwdriver

Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — KI5210 — 06.03.2003