

Product characteristics

Capacitive sensor

Metal thread M34 x 1.5

Cable

ATEX approval

Group II, category 1D/1G

Sensing range 15 mm; adjustable; [nf] non-flush mountable

Electrical data

Electrical design

Connection to certified intrinsically safe circuits with the max. values  $U = 15 \text{ V} / I = 50 \text{ mA} / P = 120 \text{ mW}$

Nominal voltage [V]

8.2 DC; (1k $\Omega$ )

Supply voltage [V]

7.5...15 DC

Current consumption [mA]

< 1.0 disabled; (> 2.2 mA enabled)

Protection class

I

Outputs

Output function

normally closed

Switching frequency [Hz]

40

Monitoring range

Sensing range [mm]

15, adjustable

Accuracy / deviations

Correction factors

water = 1 / glass approx. 0.4 / ceramics approx. 0.2 / PVC approx. 0.2

Hysteresis [% of Sr]

1...15

Switch-point drift [% of Sr]

-15...15

Environment

Ambient temperature [°C]

-20...60

Protection

IP 65

Tests / approvals

Approval

DMT 01 ATEX E 020

Marking of the unit

$\text{Ex}$  II 1G Ex ia IIB T6 Ga

$\text{Ex}$  II 1D Ex ia IIIC T90 °C Da

EMC

IEC 60947-5-2:

2007

MTTF [Years]

838

Safety classification

Internal capacitance [nF]

375.64

Internal inductance [ $\mu\text{H}$ ]

3

Mechanical data

Mounting

non-flush mountable

Housing materials

brass white bronze coated; active face: PTFE

Weight [kg]

0.629

Displays / operating elements

Output status indication LED

yellow

Electrical connection


Connection

PVC cable / 6 m; 3 x 0.5 mm<sup>2</sup>

**Wiring**

**KX5002 - Capacitive sensor - eclass: 27270102 / 27-27-01-02**

Core colors  
BN brown  
BU blue  
GN/YE green/yellow



Remarks

Pack quantity [piece] 1