



Product availability : Stock - Normally stocked in distribution facility



### Main

Range	TeSys
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	2 NO
Connections - terminals	Screw clamp terminals 2 cable 0...0.01 in <sup>2</sup> (1.5...4 mm <sup>2</sup> ) - cable stiffness: solid Screw clamp terminals 1 cable 0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: solid Screw clamp terminals 1 cable 0...0.01 in <sup>2</sup> (0.5...6 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0...0 in <sup>2</sup> (0.35...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0.01 in <sup>2</sup> (0.35...6 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0...0 in <sup>2</sup> (0.35...1.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end

### Complementary

Mounting location	Front side
[Ui] rated insulation voltage	690 V - conforming to CSA C22.2 No 14 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 690 V - conforming to VDE 0110 group C
System Voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at <= 131 °F (55 °C)
Associated fuse rating	IEC 60947 VDE 0660
Tightening torque	7.08 lbf.in (0.8 N.m) - on screw clamp terminals
Width	1.06 in (27 mm)
Product weight	0.05 lb(US) (0.022 kg)

### Environment

Standards	BS 5424
-----------	---------

IEC 60947  
NF C 63-110  
VDE 0660

Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Ambient air temperature for storage	-58...158 °F (-50...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating in temperature

### Ordering and shipping details

Category	22371 - RELAYS, CONTROL
Discount Schedule	I12
GTIN	00785901866787
Nbr. of units in pkg.	1
Package weight(Lbs)	5.999999999999998E-2
Returnability	Y
Country of origin	CZ

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0718 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------