



Main

Range	TeSys
Device short name	LA4D
Poles description	3P
Product or component type	Interface module
Product compatibility	LC1D09...D150

Complementary

Mounting mode	Top mounted
Technology type	Electromechanical
[Us] rated supply voltage	48 V DC
Control circuit voltage limits	33...60 V at 68 °F (20 °C)
[Ui] rated insulation voltage	250 V - for control circuit - conforming to IEC 60947-5-1
Connections - terminals	Control circuit: connector 2 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - with cable end Control circuit: connector 2 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: connector 1 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: connector 1 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid - with cable end Control circuit: connector 1 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid - without cable end Control circuit: connector 2 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid - with cable end Control circuit: connector 2 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid - without cable end
System Voltage	24...250 V AC control circuit
Current consumption	15 mA 68 °F (20 °C)
Current state 0 guaranteed	<= 1.3 mA
Voltage state 0 guaranteed	< 4.8 V
Voltage state 1 guaranteed	33 V
Electrical durability	10 Mcycles at 240 V
Local signalling	LED indicator
Height	0.47 in (12 mm)
Product weight	0.11 lb(US) (0.05 kg)

Environment

Standards	IEC 60255-5
Product certifications	CSA UL
Protection type	Built-in by diode
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature around device	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Heat dissipation	0.6 W for control circuit
Immunity to microbreaks	4 ms

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901260912
Nbr. of units in pkg.	1
Package weight(Lbs)	0.12
Returnability	N
Country of origin	TN

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status

END OF COMMERCIALIZATION