



Product availability : Stock - Normally stocked in distribution facility



Main

Range	TeSys
Product or component type	Serial timer modules
Device short name	LA4DT
Poles description	3P
Product compatibility	LC1D80...D150 LC1D09...D65A

Complementary

Mounting location	Top
[Uc] control circuit voltage	24...250 V AC 50/60 Hz 24...250 V DC
Control circuit voltage limits	0.8...1.1 Uc at -13...131 °F (-25...55 °C) by mechanical contact
[Ui] rated insulation voltage	250 V - conforming to IEC 60947-1
Connections - terminals	Control circuit: connector 1 cable 0 in ² (1 mm ²) - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 0 in ² (1 mm ²) - cable stiffness: solid - with cable end Control circuit: connector 2 cable 0 in ² (2.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: connector 2 cable 0 in ² (2.5 mm ²) - cable stiffness: solid - without cable end
Electrical durability	30 Mcycles
Timer type	On delay
Time delay range	0.1...2 s
Reset time	150 ms during time delay 50 ms after time delay
Local signalling	Illuminates during time delay by LED
[Ures] residual voltage	3.3 V
Product weight	0.09 lb(US) (0.04 kg)

Environment

Standards	IEC 60255-5
Product certifications	UL CSA
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Permissible ambient air temperature around the device	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Protection type	Built-in by varistor
Heat dissipation	2 W at 50/60 Hz
Immunity to microbreaks	10 ms during time delay 2 ms after time delay

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901260981
Nbr. of units in pkg.	1
Package weight(Lbs)	0.11
Returnability	Y
Country of origin	TN

Contractual warranty

Warranty period	18 months
-----------------	-----------