



Main

| | |
|---------------------------|--|
| Range | TeSys |
| Product or component type | Serial timer modules |
| Device short name | LA4DT |
| Poles description | 3P |
| Product compatibility | 3 poles LC1D09...D38 4 poles LC1DT20...DT40 |

Complementary

| | |
|--------------------------------|--|
| Mounting location | Top |
| [Uc] control circuit voltage | 24...250 V AC 50/60 Hz 24...250 V DC |
| Control circuit voltage limits | 0.8...1.1 Uc at -13...131 °F (-25...55 °C) by mechanical contact |
| [Ui] rated insulation voltage | 250 V - conforming to IEC 60947-1 |
| Connections - terminals | Control circuit: connector 1 cable 0 in ² (1 mm ²) - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 0 in ² (1 mm ²) - cable stiffness: solid - with cable end Control circuit: connector 2 cable 0 in ² (2.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: connector 2 cable 0 in ² (2.5 mm ²) - cable stiffness: solid - without cable end |
| Electrical durability | 30 Mcycles |
| Timer type | On delay |
| Time delay range | 1.5...30 s |
| Reset time | 150 ms during time delay 50 ms after time delay |
| Local signalling | Illuminates during time delay by LED |
| [Ures] residual voltage | 3.3 V |
| Product weight | 0.09 lb(US) (0.04 kg) |

Environment

| | |
|---|--|
| Standards | IEC 60255-5 |
| Product certifications | CSA UL |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Protective treatment | TH conforming to IEC 60068 |
| Ambient air temperature for operation | -13...131 °F (-25...55 °C) |
| Permissible ambient air temperature around the device | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...176 °F (-40...80 °C) |
| Protection type | Built-in by varistor |
| Heat dissipation | 2 W at 50/60 Hz |
| Immunity to microbreaks | 10 ms during time delay 2 ms after time delay |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22341 - CONTACTOR,D,K,&F ACCESS |
| Discount Schedule | I12 |
| GTIN | 00785901260998 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.10000000000000001 |
| Returnability | Y |
| Country of origin | TN |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|