



## Main

|                                |   |
|--------------------------------|---|
| Range of product               | TeSys D   |
| Range                          | TeSys   |
| Product name                   | TeSys D   |
| Product or component type      | Contactor   |
| Device short name              | LC1D  |
| Contactor application          | Motor control<br>Resistive load   |
| Utilisation category           | AC-3<br>AC-1<br>AC-4  |
| Poles description              | 3P  |
| Pole contact composition       | 3 NO  |
| System Voltage                 | $\leq 300$ V DC power circuit<br>$\leq 1000$ V AC 25...400 Hz power circuit   |
| [Ie] rated operational current | 200 A ( $\leq 140$ °F (60 °C)) at $\leq 440$ V AC AC-1 power circuit<br>150 A ( $\leq 140$ °F (60 °C)) at $\leq 440$ V AC AC-3 power circuit  |
| Motor power kW                 | 40 kW at 220...230 V AC 50/60 Hz AC-3<br>75 kW at 380...400 V AC 50/60 Hz AC-3<br>80 kW at 415...440 V AC 50/60 Hz AC-3<br>90 kW at 500 V AC 50/60 Hz AC-3<br>100 kW at 660...690 V AC 50/60 Hz AC-3<br>75 kW at 1000 V AC 50/60 Hz AC-3<br>22 kW at 400 V AC 50/60 Hz AC-4 |
| Motor power hp                 | 40 hp at 200/208 V AC 50/60 Hz 3 phases motors<br>50 hp at 230/240 V AC 50/60 Hz 3 phases motors<br>100 hp at 460/480 V AC 50/60 Hz 3 phases motors<br>125 hp at 575/600 V AC 50/60 Hz 3 phases motors  |
| Control circuit type           | AC 50/60 Hz   |
| [Uc] control circuit voltage   | 120 V AC 50/60 Hz   |
| Auxiliary contact composition  | 1 NO + 1 NC   |

|   |  |
|---|--|
| [Uimp] rated impulse withstand voltage      | Conforming to IEC 60947  |
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 200 A at <= 140 °F (60 °C) power circuit   |
| Irms rated making capacity                  | 1660 A at 440 V power circuit conforming to IEC 60947<br>140 A AC signalling circuit conforming to IEC 60947-5-1<br>250 A DC signalling circuit conforming to IEC 60947-5-1  |
| Rated breaking capacity                     | 1400 A at 440 V power circuit conforming to IEC 60947  |
| [Icw] rated short-time withstand current    | 100 A 1 s signalling circuit<br>120 A 500 ms signalling circuit<br>140 A 100 ms signalling circuit<br>250 A <= 104 °F (40 °C) 10 min power circuit<br>580 A <= 104 °F (40 °C) 1 min power circuit<br>1200 A <= 104 °F (40 °C) 10 s power circuit<br>1400 A <= 104 °F (40 °C) 1 s power circuit   |
| Associated fuse rating                      | 250 A gG at <= 690 V coordination type 2 power circuit<br>315 A gG at <= 690 V coordination type 1 power circuit<br>10 A gG signalling circuit conforming to IEC 60947-5-1   |
| Average impedance                           | 0.6 mOhm at 50 Hz - Ith 200 A power circuit  |
| [Ui] rated insulation voltage               | 1000 V power circuit conforming to IEC 60947-4-1<br>600 V power circuit certifications CSA<br>600 V power circuit certifications UL<br>690 V signalling circuit conforming to IEC 60947-1<br>600 V signalling circuit certifications CSA<br>600 V signalling circuit certifications UL   |
| Electrical durability                       | 0.85 Mcycles 150 A AC-3 at Ue <= 440 V<br>1 Mcycles 200 A AC-1 at Ue <= 440 V  |
| Power dissipation per pole                  | 24 W AC-1<br>13.5 W AC-3   |
| Protective cover                            | With   |
| Mounting support                            | Rail<br>Plate  |
| Standards                                   | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508  |
| Product certifications                      | BV<br>DNV<br>UL<br>GOST<br>CCC<br>RINA<br>GL<br>LROS<br>CSA  |
| Connections - terminals                     | Control circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Power circuit: connector 1 cable(s) 0.02...0.19 in <sup>2</sup> (10...120 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Power circuit: connector 2 cable(s) 0.02...0.08 in <sup>2</sup> (10...50 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Power circuit: connector 1 cable(s) 0.02...0.19 in <sup>2</sup> (10...120 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: connector 2 cable(s) 0.02...0.08 in <sup>2</sup> (10...50 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: connector 1 cable(s) 0.02...0.19 in <sup>2</sup> (10...120 mm <sup>2</sup> ) - cable stiffness: solid - without cable end |

Power circuit: connector 2 cable(s) 0.02...0.08 in<sup>2</sup> (10...50 mm<sup>2</sup>) - cable stiffness: solid - without cable end

|                          |  |
|--------------------------|--|
| Tightening torque        | Control circuit: 10.62 lbf.in (1.2 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 10.62 lbf.in (1.2 N.m) - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 106.19 lbf.in (12 N.m) - on connector hexagonal 0.16 in (4 mm) |
| Operating time           | 20...35 ms closing<br>40...75 ms opening   |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |
| Mechanical durability    | 8 Mcycles  |
| Operating rate           | 1200 cyc/h at ≤ 140 °F (60 °C)   |

## Complementary

|                                 |  |
|---------------------------------|--|
| Coil technology                 | Built-in bidirectional peak limiting diode suppressor  |
| Control circuit voltage limits  | 0.3...0.5 U <sub>c</sub> drop-out at 131 °F (55 °C), AC 50/60 Hz<br>0.8...1.15 U <sub>c</sub> operational at 131 °F (55 °C), AC 50/60 Hz |
| Inrush power in VA              | 280...350 VA at 68 °F (20 °C) (cos φ 0.9) 60 Hz<br>280...350 VA at 68 °F (20 °C) (cos φ 0.9) 50 Hz                                       |
| Hold-in power consumption in VA | 2...18 VA at 68 °F (20 °C) (cos φ 0.9) 60 Hz<br>2...18 VA at 68 °F (20 °C) (cos φ 0.9) 50 Hz   |
| Heat dissipation                | 3...4.5 W at 50/60 Hz  |
| Auxiliary contacts type         | Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1<br>Type mirror contact (1 NC) conforming to IEC 60947-4-1             |
| Signalling circuit frequency    | 25...400 Hz  |
| Minimum switching current       | 5 mA signalling circuit  |
| Minimum switching voltage       | 17 V signalling circuit  |
| Non-overlap time                | 1.5 ms on de-energisation (between NC and NO contact)<br>1.5 ms on energisation (between NC and NO contact)                              |
| Insulation resistance           | > 10 MOhm signalling circuit   |

## Environment

|   |   |
|---|---|
| IP degree of protection                               | IP2x front face conforming to IEC 60529   |
| Protective treatment                                  | TH conforming to IEC 60068-2-30   |
| Pollution degree                                      | 3   |
| Ambient air temperature for operation                 | 23...140 °F (-5...60 °C)  |
| Ambient air temperature for storage                   | -76...176 °F (-60...80 °C)  |
| Permissible ambient air temperature around the device | -40...158 °F (-40...70 °C) at U <sub>c</sub>  |
| Operating altitude                                    | 9842.52 ft (3000 m) without derating in temperature   |
| Fire resistance                                       | 1562 °F (850 °C) conforming to IEC 60695-2-1  |
| Flame retardance                                      | V1 conforming to UL 94  |
| Mechanical robustness                                 | Vibrations contactor open 2 Gn, 5...300 Hz<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open 6 Gn for 11 ms |
| Height  | 6.22 in (158 mm)  |
| Width   | 4.72 in (120 mm)  |
| Depth   | 5.35 in (136 mm)  |
| Product weight  | 5.51 lb(US) (2.5 kg)  |

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22345 - CTR,D-LINE,OPEN,NONREV-NEW |
| Discount Schedule     | I12                                |
| GTIN                  | 00785901214519                     |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 5.4400000000000004                 |

|                   |    |
|-------------------|----|
| Returnability     | Y  |
| Country of origin | CZ |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0932 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Available   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|